



# Compact and agile for small areas

## RA 300 E 2 disc brushes

The ideal compact machine for smaller areas of all types of hard floor. The two disc brushes thoroughly scrub the floor, and the dirty solution is immediately extracted via squeegee system. With adjustable handle.

Art. 300.000



**Technical data:**

Total power	1200 W
Vacuum	180 mbar
Fresh water capacity	13 liters
Dirty water capacity	16 liters
Suction width	39 cm
Working width	35 cm
Productivity rate theoretical	1320 m <sup>2</sup> /h
Brush pressure	10 kg
Brush diameter	2 x 17 cm
Cable length	7,5 m
Weight	22 kg
Measurements l/w/h	55/39/46 cm
Squeegee lifter	incl.

**Complete incl.:**

320.059	Disc brush Ø 16,5 cm (2 pieces needed)
300.420	Vacuum nozzle complete (2 pieces needed)

**Special accessories:**

300.070	Driving disc, Ø 16,5 cm (2 pieces needed)
300.010.10	Pad red, Ø 16,5 cm, 10 pieces
300.025.10	Pad blue, Ø 16,5 cm, 10 pieces
300.020.10	Pad brown, Ø 16,5 cm, 10 pieces
300.030	Micro fibre pad, Ø 16,5 cm, 1 piece
300.0595K	Disc brush, 5K, Ø 17 cm, 1 piece
300.060	Accessories-kit:
380.060	Spray and suction hose, 3 m
606.000.2	Carpet tool, 1 jet 23 cm with plastic handtube
P600W	Hard floor nozzle
681.000	Filling up hose for fresh water, 2 m



RA 300 E:  
Removable tank



Accessory Kit



Fully adjustable telescopic handle



Easy removable squeegees

## RA 330 IBC 2 disc brushes

Machine with one 12 V battery and internal charger and two 12 lt tanks. This autoscrubber is very habil and maneuverable and for this reason perfect for all kind of hard floors in small areas (like cloakrooms). The machine has two scrubbing brushes to ensure real scrubbing efficiency. With a suction nozzle in the front and on the back you can absorb the dirt very well and you can work forward and backwards.

Art. 330.000



Video



**Technical data:**

Working width	33 cm
Power suction motor	300 W / 12 V
Power brush motor	150 W
Brush speed	240 rpm
Brush pressure	17 kg
Battery capacity	25 Ah
Autonomie (max.)	0,9 h
Fresh water capacity	12 liters
Dirty water capacity	11 liters
Weight (with battery)	35 kg
Chargin time	8 h
Productivity rate theoretical	1320 m <sup>2</sup> /h
Measurements l/w/h	47/37/55 cm

**Complete incl.:**

320.059	Disc brush (2 pieces needed), Ø 16,5 cm
330.091	Battery 12V/33 Ah (19,5 x 13 x 18 cm)
330.092	Battery charger
320.421	Suction nozzle

**Special accessories:**

300.070	Driving disc (2 pieces needed), Ø 16,5 cm
300.010.10	Pad red, Ø 16,5 cm, 10 pieces
300.025.10	Pad blue, 16,5cm, 10 pieces
300.020.10	Pad brown, Ø 16,5 cm, 10 pieces
300.030	Micro fibre pad, Ø 16,5 cm, 1 piece
300.0595K	Disc brush, 5K, Ø 16,5 cm, 1 piece
681.000	Filling up hose for fresh water, 2 m



Ideal for narrow corridors



Fully adjustable telescopic handle



Two removable tanks



RA 330 IBC integrated measuring cup

# Powerful and handy

## RA 410 E 1 cylindrical brush

Perfect results on all types of hard floors with the cylindrical brush plus twin retractable squeegees. It scrubs and dries both forward and backwards. With adjustable handle.

Art. 411.000 (while stocks last)



**Technical data:**

Total power	1200 W / 230 V
Vacuum	215 mbar
Fresh water capacity	33 liters
Dirty water capacity	38 liters
Suction width	44 cm
Brush width	33 cm
Productivity rate theoretical	1320 m <sup>2</sup> / h
Brush pressure	12 kg
Working width	33 cm
Weight	38 kg
Cable length	20 m
Measurements l / w / h	97 / 48 / 70 cm
Squeegee lifter	incl.

**Complete incl.:**

400.470	Cylindrical brush standard, 33 cm
400.784	Water bucket, 12 liters
411.750	Fresh water drain hose
400.520	Vacuum nozzle compl., front
400.530	Vacuum nozzle compl., back
500.863	Power cable, 20 m, 3 x 1 mm <sup>2</sup>

**Special accessories:**

681.000	Filling up hose for fresh water, 2m
400.472	Brush hard, 33 cm
420.011	Spray and vacuum hose, 5 m
606.000.2	Carpet tool, 1 jet 23 cm with plastic hand tube
606.000.3	Carpet tool, 1 jet 23 cm with inox tube
P600W	Hard floor nozzle
400.050	Set of lamella compl.



RA 410 E Maximum capacity with membrane tank



Adapter connection for cleaning in narrow places and stairs



Hardfloor tool



Simple clear controls



# Powerful and compact

**RA 431 E**  
**RA 431 B (Battery)**  
**RA 431 IBC**  
**(Integrated Battery Charger)**

Very tough scrubbing machine for middle-sized floor space in business and industry. Optimum cleaning results with high brush pressure. With big wheels the machine runs vibration free and copes well with obstacles. The machine pulls itself forward by using the brush rotation.

RA 431 E:	Art. 432.000
RA 431 B:	Art. 436.000
RA 431 IBC:	Art. 436.015

**Technical data RA 431 E:**

Power supply	~ 230 V / 50 Hz
Power brush motor	1100 W
Power suction motor	750 W
Vacuum	140 mbar
Fresh water capacity	35 liters
Dirty water capacity	40 liters
Suction width	76 cm
Working width	43 cm
Productivity rate theoretical	1750 m <sup>2</sup> / h
Brush pressure	34 kg
Brush speed	180 rpm
Weight	62 kg
Measurements l/w/h	80 / 43 / 73 cm
Cable length	20 m

**Technical data RA 431 B / RA 431 IBC:**

Power supply	24 V DC
Power brush motor	750 W
Power suction motor	400 W
Vacuum	110 mbar
Fresh water capacity	32 liters
Dirty water capacity	38 liters
Suction width	76 cm
Productivity rate theoretical	1750 m <sup>2</sup> / h
Working width	43 cm
Brush pressure	47 kg
Brush speed	150 rpm
Weight (without battery)	48 kg
Weight (with battery)	122 kg
Measurements l/w/h	85 / 43 / 80 cm

**Complete incl.:**

742.059	Scrubbing brush PPN 0.6, Ø 43 cm
500.863	Power cable, 20 m, 3 x 1 mm <sup>2</sup>

**Accessories RA 431 E:**

432.031	Suction nozzle, standard, complete incl. suction hose
432.032	Suction nozzle curved oil and grease resistant

**Accessories RA 431 B / RA 431 IBC:**

432.031	Suction nozzle, standard, complete incl. suction hose
432.033	Suction nozzle curved oil and grease resistant

**Accessories:**

681.000	Filling up hose for fresh water, 2m
742.070	Driving disc, 180 rpm, Ø 39 cm
742.073	Exposed aggregate pavement brush, Ø 43 cm
742.0595K	Scrubbing brush PPN 0.6 5K, Ø 43 cm
742.076	Silicium Carbid brush
694.321.5	Pad white, Ø 43,2 cm, 5 pieces
694.322.5	Pad red, Ø 43,2 cm, 5 pieces
694.323.5	Pad blue, Ø 43,2 cm, 5 pieces
694.324.5	Pad brown, Ø 43,2 cm, 5 pieces
694.325.5	Pad black, Ø 43,2 cm, 5 pieces
694.327	Micro fibre pad, Ø 43,2 cm
432.551	Rubber blade oil resistant (Suction nozzle curved)
432.552	Rubber blade standard (Suction nozzle curved)
500.091	Set of Gel batteries à 12 V/76 Ah (C5) (330 x 171 x 236 mm)
686.100	Battery charger 24V / 12A VDE



Large filling hole



Easy brush assembly



Easy emptying



Rubber blade set



Water regulator



Motor cut off

# Powerful and compact



## RA 433 IBC (Integrated Battery Charger)

Innovative and robust scrubber dryer for middle sized floors in crafts and industries. Ideal cleaning efficiency due to high brush pressure. The big sized wheels ensure a vibration free drive of the machine. Traction occurs via brush rotation, means the machine pushes forward independently.

Art. 433.015

**Technical data:**

Power supply	24 V DC
Power brush motor	750 W
Power suction motor	400 W
Vacuum	110 mbar
Fresh water capacity	32 liters
Dirty water capacity	38 liters
Suction width	53 cm
Working width	43 cm
Productivity rate theoretical	1750 m <sup>2</sup> / h
Brush pressure	47 kg
Weight without battery	64 kg
Weight with battery	122 kg
Measurements l/w/h	85 / 43 / 80 cm

**Complete incl.:**

742.059	Scrubbing brush PPN 0.6, Ø 43 cm
433.108	Suction nozzle, standard, complete incl. suction hose

**Special accessories:**

681.000	Filling up hose for fresh water, 2m
742.070	Driving disc, 180 rpm, Ø 39 cm
790.070A	Driving disc High-Speed with rubber element
752.070 A	Driving disc, high speed
742.072	Polishing brush Mexican Fibre
742.073	Exposed aggregate pavement brush
742.0595K	Scrubbing brush PPN 0.6 5K, Ø 43 cm
742.076	Silicium Carbid brush
694.321.5	Pad white, Ø 43,2 cm, 5 pieces
694.322.5	Pad red, Ø 43,2 cm, 5 pieces
694.323.5	Pad blue, Ø 43,2 cm, 5 pieces
694.324.5	Pad brown, Ø 43,2 cm, 5 pieces
694.325.5	Pad black, Ø 43,2 cm, 5 pieces
694.326	Pad high speed, Ø 43 cm natural fibres
694.327	Micro fibre pad, Ø 43,2 cm
433.081	Rubber blade oil and frease resistant (Suction nozzle curved)
433.082	Rubber blade standard (Suction nozzle curved)
500.091	Set of Gel batteries à 12 V/76 Ah (C5) (330 x 171 x 236 mm)



On the reverse of the handle is a switch for the two speeds.



Easy to empty



Rubber blade set



Water volume control



Motor cut off

# Powerful and compact

## RA 501 E

## RA 501 B (Battery)

## RA 501 IBC

Very tough scrubbing machine for middle-sized floor space in business and industry. Optimum cleaning results with high brush pressure. With big wheels the machine runs vibrationfree and copes well with obstacles. The machine pulls itself forward by using the brush rotation.

RA 501 E:	Art. 501.000
RA 501 B:	Art. 501.010
RA 501 IBC:	Art. 501.015

### Technical data RA 501 E:

Power supply	~ 230 V / 50 Hz
Power brush motor	1100 W
Power suction motor	750 W
Vacuum	190 mbar
Fresh water capacity	35 liters
Dirty water capacity	40 liters
Suction width	82 cm
Working width	50 cm
Productivity rate theoretical	2100 m <sup>2</sup> /h
Brush pressure	34 kg
Brush speed	180 rpm
Weight	62 kg
Measurements l/w/h	80/51/73 cm
Cable length	20 m

### Technical data RA 501 B/RA 501 IBC:

Power supply	24 V DC
Power brush motor	1000 W
Power suction motor	400 W
Vacuum	130 mbar
Fresh water capacity	32 liters
Dirty water capacity	38 liters
Suction width	82 cm
Working width	50 cm
Productivity rate theoretical	2100 m <sup>2</sup> /h
Brush pressure	48 kg
Brush speed	135 rpm
Weight (without battery)	54 kg
Weight (with battery)	122 kg
Measurements l/w/h	85/51/80 cm

### Complete incl.:

730.059	Scrubbing brush PPN 0,6, Ø 51 cm
500.863	Power cable, 20 m, 3 x 1 mm <sup>2</sup>

### Accessories RA 501 E:

432.031	Suction nozzle, standard, complete incl. suction hose
432.032	Suction nozzle curved oil and grease resistant

### Accessories RA 501 B/RA 501 IBC:

432.031	Suction nozzle, standard, compl. incl. suction hose
432.033	Suction nozzle curved oil and grease resistant

### Special accessories:

681.000	Filling up hose for fresh water, 2 m
730.0595K	Scrubbing brush 5K Ø 51 cm
730.070	Driving disc Ø 47 cm
730.073	Exposed aggregate pavement brush Ø 51 cm
730.476	Silicium Carbid brush
695.087.5	Pad red, Ø 50,8 cm, 5 pieces
695.088.5	Pad blue, Ø 50,8 cm, 5 pieces
695.089.5	Pad brown, Ø 50,8 cm, 5 pieces
432.551	Rubber blade oil resistant (Suction nozzle curved)
432.552	Rubber blade standard (Suction nozzle curved)
500.091	Set of Gel batteries à 12 V/76 Ah (C5) (330 x 171 x 236 mm)
686.100	Battery charger 24V / 12A VDE



Large filling hole



Easy brush assembly



Easy emptying



Rubber blade set



Water regulator



Motor cut off

# Agile and user friendly

## RA 505 IBC (Integrated battery charger)

Shapely, robust scrubber dryer, ideal for hard and flexible floors for industries, retail and public environments. Traction occurs via brush rotation, means the machine pushes forward independently. All operational controls are very user friendly – a brush change is carried out in seconds. Ideal for middle sized surfaces.

Art. 555.015



Video



Leaflet

### Technical data:

Traction via brush rotation, means the machine pushes forward self-dependent.	
Power supply	24 V DC
Power brush motor	750 W
Power suction motor	400 W
Vacuum	130 mbar
Fresh water capacity	55 liters
Dirty water capacity	56 liters
Suction width	88 cm
Working width	51 cm
Productivity rate theoretical	2100 m <sup>2</sup> /h
Brush pressure	48 kg
Brush diameter	51 cm
Weight incl. batteries	164 kg
Measurements l/w/h	145/56/113 cm

### Complete incl.:

730.059	Scrubbing brush Ø 51 cm
555.560	Suction nozzle curved

### Special Accessories:

681.004	Filling up hose for fresh water 1,6 m
555.070	Driving disc Ø 47 cm
730.0595K	Scrubbing brush 5K Ø 51 cm
730.073	Exposed aggregate pavement brush Ø 51 cm
730.476	Silicium Carbide brush Ø 51 cm
695.087.5	Pad red, Ø 50,8 cm, 5 pieces
695.088.5	Pad blue, Ø 50,8 cm, 5 pieces
695.089.5	Pad brown, Ø 50,8 cm, 5 pieces
565.082	Rubber blade standard
565.081	Rubber blade oil resistant
530.091	Set of 2 Gel batteries à 12 V / 105 Ah (C5) (345 x 172 x 283 mm)
565.535	Canister 5 liters empty



- + Easy handling suction nozzle
- + Integrated battery charger
- + Traction via brush rotation
- + close turning radius
- + silent working



Suction unit is very easy to use



The operator can always see inside the tank



Easy to open and to clean



Easy access to the batteries.



The brush can be fixed



Edge cleaning, easy as pie, whether along borders, frames or palletes, the machine adapts to the circumstances



# Agile and clearly

## RA 505 IBCT (Integrated battery charger and forward and backwards traction)

Shapely, robust scrubber dryer, ideal for hard and flexible floors for industries, retail and public institutions. Forward/backwards working possible. The RA 505 IBCT has a automatic traction, as well as environmentally friendly chemical dosing with the Cleanfix-Dosing-System (optional), ensures a high user friendliness. Ideal for middle sizes surfaces.

Art. 555.055	without chemical dosing system CADS
Art. 555.010	with chemical dosing system CADS



Video



Leaflet

### Technical data:

Automatic traction via traction motor	
Power supply	24 V DC
Power brush motor	750 W
Power suction motor	400 W
Vacuum	130 mbar
Fresh water capacity	55 liters
Dirty water capacity	56 liters
Suction width	88 cm
Working width	51 cm
Productivity rate theoretical	2100 m <sup>2</sup> /h
Brush pressure	48 kg
Brush diameter	51 cm
Weight incl. batteries	178 kg
Measurements l/w/h	145/56/113 cm

### Complete incl.:

730.059	Scrubbing brush, Ø 51 cm
555.560	Suction nozzle curved

### Special accessories:

681.004	Filling up hose for fresh water, 1,6 m
555.070	Driving disc
730.0595K	Scrubbing brush 5K, Ø 51 cm
730.073	Exposed aggregate pavement brush, Ø 51 cm
730.476	Silicium Carbide brush, Ø 51 cm
695.087,5	Pad red, Ø 50,8 cm, 5 pieces
695.088,5	Pad blue, Ø 50,8 cm, 5 pieces
695.089,5	Pad brown, Ø 50,8 cm, 5 pieces
565.081	Rubber blade oil resistant
565.082	Rubber blade standard
530.091	Set of 2 Gel batteries à 12 V / 105 Ah (C5) (345 x 172 x 283 mm)
565.535	Canister 5 liters empty
565.267	Tractionwheel (2 pieces needed)



- + Easy handling suction nozzle
- + Easy understandable display
- High cleaning power
- + Integrated battery charger
- + Forward and backwards traction
- + automatical water dosing, depends on speed
- + Chemical saving with Cleanfix dosing system (optional)



Suction unit is very easy to use



The operator can always see inside the tank



Clearly laid out control panel



Chemical dosing easy to set



The floater works at the same time as overflow protection



Retainer for 5 lts. Canister



Optional filling hose is always with the machine. With this, the clean water tank can be filled from every tap.



# Modern and powerful



## RA 605 IBCT (Integrated battery charger and forward and backwards traction)

Shapely, robust scrubber dryer, ideal for hard and flexible floors for industries, retail and public environments. Two contra-rotating brushes for streak-free cleaning. Automatic traction, as well as environmentally friendly chemical dosing with the Cleanfix-Dosing-System (optional), ensures a high user friendliness. Ideal for bigger surfaces.

Art. 565.055	without chemical dosing system CADS
Art. 565.010	with chemical dosing system CADS



Video



Leaflet

### Technical data:

Power supply	24 V DC
Power brush motor	750 W
Power suction motor	400 W
Vacuum	130 mbar
Fresh water capacity	55 liters
Dirty water capacity	56 liters
Suction width	88 cm
Working width	60 cm
Productivity rate theoretical	2500 m <sup>2</sup> /h
Brush pressure	55 kg
Brush diameter	2 x 31 cm
Weight incl. batteries	190 kg
Measurements l/w/h	138/64/113 cm

### Complete incl.:

565.059	Scrubbing brushes, Ø 31 cm (2 pieces needed)
555.560	Suction nozzle curved

### Special accessories:

681.004	Filling up hose for fresh water, 1,6 m
565.535	Canister 5 liters empty
565.430	Compl. chemical dosing, incl. assembling
565.082	Rubber blade, standard
565.081	Rubber blade oil resistant
565.070	Driving disc (2 pieces needed)
565.073	Exposed aggregate pavement brush, Ø 31 cm (2 pieces needed)
565.074	Exposed aggregate pavement brush, fine (2 pieces needed)
565.076	Silicium Carbide brush, Ø 31 cm
693.052,5	Pad red, Ø 30,5 cm, 5 pieces
693.053,5	Pad blue, Ø 30,5 cm, 5 pieces
693.054,5	Pad brown, Ø 30,5 cm, 5 pieces
530.091	Set of 2 Gel batteries à 12 V / 105 Ah (C5) (345 x 172 x 283 mm)
565.267	Tractionwheel (2 pieces needed)



- + Easy handling suction nozzle
- + Easy understandable display
- + High cleaning power
- + Integrated battery charger
- + Forward and backwards traction
- + automatical water dosing, depends on speed
- + Chemical saving with Cleanfix dosing system (optional)



Suction unit is very easy to use



The operator can always see inside the tank



Clearly laid out control panel



Chemical dosing easy to set



The floater works at the same time as overflow protection



Retainer for 5 lts. Canister

# Small and manoeuvrable

## RA 535 IBCT Including chemical dosing system CADS

Ride comfortably instead of walking along behind – this is what the ride-on scrubber dryer RA 535 IBCT has to offer. The RA 535 IBCT is smaller and more manoeuvrable than expected. Ideal for cleaning hard and rubberized floors of medium-size in industry, commerce and public institutions. With chemical dosing system CADS.

Art. 535.000

incl. integrated battery charger



Video



Leaflet

### Technical data:

Power supply	24 V DC
Power traction motor	400 W
Power brush motor	400 W
Power suction motor	400 W
Working width	53 cm
Suction width	60 cm
Turning radius	150 cm
Vacuum	115 mbar
Fresh water capacity	55 liters
Dirty water capacity	55 liters
Brush speed	175 rpm
Working speed	3-6 km/h
Maximum speed	6 km/h
Productivity rate theoretical	3180 m <sup>2</sup> /h
Autonomie max.	2,3 h
Weight empty	148 kg
Protection class	IPX4
Noise level	64 db (A)
Measurements l/w/h	127 x 65 x 113 cm

### Complete incl.:

535.059	Scrubbing brush, Ø 53 cm
535.250	Traction wheel „supergrip“ standard
535.440	Filtre cartridge standard
535.082	Rubber blade standard
535.560	Suction nozzle curved
535.100	Compl. Chemical dosing system

### Special accessories:

535.0595K	5K brush (supermarket mix)
535.073	Exposed aggregate pavement brush
535.070	Driving disc
535.910,5	Pad red, Ø 53 cm, 5 pcs.
535.911,5	Pad blue, Ø 53 cm, 5 pcs.
535.912,5	Pad brown, Ø 53 cm, 5 pcs.
530.091	Set of 2 Gel batteries à 12 V / 105 Ah (C5) (345 x 172 x 283 mm)
535.110	Filling up hose for fresh water
535.081	Rubber blade oil resistant
535.083	Rubber blade linatex (tile floors)
535.450	Hepa filter cartridge
535.130	divider wall dirty water tank

- + Ergonomically seat
- + Clear operating panel
- + With integrated charger
- + With S-DOSE Speed Variable Dosing, speed-dependent provision of cleaning solution
- + Standard with CADS
- + Changing batteries in less than 5 minutes
- + Suction bas beneath the vehicle, cannot get stuck
- + Twice as fast as a walk-behind model
- + Fits into every elevator thanks to narrow passage width



Comfortable seat



Suction base mounted directly behind the brush



Operating panel with charge indicator



Dirty water tank easy to clean



Rear view with fresh- and waste water tank discharge







# The ride-on model

## RA 800 sauber

Our RA sauber shows its power where we ask for manoeuvrability and speed. The sauber drives through doors with a width of 80 cm, has a good turning circle and is 50% faster than a walk behind scrubber. Due to the four wheels, a drive in the back, the machine is comfortable low to get on. The construction of the machine is very stable and robust.

Art. 800.000 without chemical dosing system CADS

**Technical data:**

Total power	2150 W
Vacuum	160 mbar
Fresh water capacity	130 liters
Dirty water capacity	135 liters
Suction width	105 cm
Working width	76 cm
Productivity rate theoretical	6400 m <sup>2</sup> / h
Brush diameter	2 x 38 cm
Turning circle	210 cm
Weight complt.	560 kg
Measurements l/w/h	172/72/132 cm
Autonomy	approx. 4 h

**Complete incl.:**

800.059	Scrubbing brush, Ø 38 cm (2 pieces needed)
800.550	Suction nozzle bent

**Special accessories:**


800.070	Pad holder (2 pieces needed)
800.476	Silicium Carbid brush (2 pieces needed)
800.573	Exposed aggregate pavement brush (2 pieces needed)
800.902.5	Pad red, Ø 38,1 cm, 5 pieces
800.903.5	Pad blue, Ø 38,1 cm, 5 pieces
800.904.5	Pad brown, Ø 38,1 cm, 5 pieces
800.640	filter for raw parts
800.081	Rubber blade, oil resistant
800.082	Rubber blade, standard
800.562	Fender wheel
800.091	4 x gel battery Dryfit à 6 V / 240 Ah (312 x 182 x 359 mm)
686.800	Gel battery charger for Dryfit 24 V / 35 A VDE

**Accessories for street legal:**


800.925	Kit for street legal, without assembling:
	Warning light yellow
	Breakdown triangle with holder
	Licence tag holder
	Tag speed limit < 10 km/h
	Reflector



Machine open showing the batteries



2 vacuum motors



Narrow turning radius



Scale for fresh water tank



Filter for raw parts



# Maximum performance



## RA 900 sauber

Our RA sauber shows its power where we ask for manoeuvrability and speed. The machine is comfortable low to get on. The construction is very stable and robust. Safety is guaranteed due to the for wheels and a drive in the back. A 130 liters water capacity will offer the right quantity of water used for the cleaning task to be done.

Art. 910.000	without chemical dosing system CADS
Art. 910.010	with chemical dosing system CADS

**Technical data:**

Total power	2150 W
Vacuum	160 mbar
Fresh water capacity	130 liters
Dirty water capacity	135 liters
Suction width	105 cm
Working width	86 cm
Productivity rate theoretical	7200 m <sup>2</sup> / h
Brush diameter	2 x 43 cm
Turning circle	210 cm
Weight compl.	500 kg
Measurements l/w/h	172/90/132 cm
Autonomy	approx. 4 h

**Complete incl.:**

910.059	Scrubbing brush, Ø 43 cm (2 pieces needed)
800.550	Suction nozzle bent

**Special accessories:**

910.070	Pad holder (2 pieces needed)
910.476	Silicium Carbid brush (2 pieces needed)
694.322.5	Pad red, Ø 43,2 cm, 5 pieces
694.323.5	Pad blue, Ø 43,2 cm, 5 pieces
694.324.5	Pad brown, Ø 43,2 cm, 5 pieces
694.325.5	Pad black, Ø 43,2 cm, 5 pieces
800.640	filter for raw parts
800.562	Fender wheel
800.081	Rubber blade, oil resistant
800.082	Rubber blade, standard
910.071	Rubber blade brush head, standard
910.072	Rubber blade brush head, oil resistant
910.573	Exposed aggregate pavement brush
800.091	4 x gel battery Dryfit à 6 V / 240 Ah (312 x 182 x 359 mm)
686.800	Gel battery charger for Dryfit 24 V / 35 A VDE

**Accessories for street legal:**

800.925	Kit for street legal, without assembling:
	Warning light yellow
	Breakdown triangle with holder
	Licence tag holder
	Tag speed limit < 10 km/h
	Reflector




Swivelling brush head allows borderless cleaning



Solid protection system



Panel: Simple and functional



2 suction motors for maximum suction



Scale for fresh water tank



Easy recharge of batteries